

# PowerWind 100

---

The PowerWind 100 is a highly efficient and robust wind turbine with a rated power of 2500 kW. Under IEC wind class IIIA and DIBt WZ II certification the PowerWind 100 is the ideal application for sites with less wind. Its 100 m rotor enables maximum output even at lower wind speeds.

Our “German Engineering” combines robust mechanical design with state-of-the-art power electronics. The PowerWind 100 is modeled after the proven modular drive train concept. Its favorable system design benefits from many years of experience gained in the wind power industry and the reliability of the PowerWind 56. Wear & tear and loads have been consequently minimized. Thanks to its full scale converter the PowerWind 100 can comply with the most demanding grid requirements and can also be connected to weaker grids. The optimal combination between rotor, generator, converter, and control system maximizes the energy output. The advanced cooling system allows for smooth operation even under unfavorable climate conditions. Its outstanding grid integration in combination with its high energy yield, unsurpassed reliability, and easy servicing make the PowerWind 100 the next generation’s wind energy converter.



PowerWind 100

**The mechanical engineering and uncompromised robustness of the PowerWind 100 assure highest durability and reliability.**

- Design based on proven modular drive train concept
- All main components sourced from reputable European manufacturers with highest longevity standards
- High reliability due to the combination of technically proven components
- Optimized mechanical structure through the application of multi-body simulation methods

**The sophisticated gearbox protection concept shields the gearbox from high loads.**

- Optimal load flow and load transfer secured by two main bearings and deformation-resistant machine frame
- Constraint loads reduced by using a maintenance-free hydraulic gearbox support
- Drive train load reduction by decoupling from the electrical grid

**The full scale converter allows compliance with the most demanding grid requirements.**

- Smooth integration in current and future wind farm configurations
- Extended reactive power capability for fast voltage control
- Excellent fault ride through capability
- Compatible with 50 Hz and 60 Hz grids

**The PowerWind 100 delivers unsurpassed reliability, easy servicing, and high availability at all wind and weather conditions.**

- Large number of technically proven standard components assuring fast and long-term availability of high quality components from multiple suppliers
- Automatic lubrication of pitch, yaw, and generator bearings
- Dust protection through internal gearings
- User-friendly global remote monitoring (SCADA)
- State-of-the-art operational plant management and safety concept

**The PowerWind 100 provides more yield than comparable turbines in its class.**

- No rotor power losses by using a permanent magnet synchronous generator
- Aerodynamically-optimized blade profile
- Efficient control algorithms throughout the full range of production
- Optimal rotor, generator, converter, and control system combination for maximum output

**Conceptual design and low sound emission minimize the environmental impact of the PowerWind 100.**

- Optimized blade tip speed for low sound emission
- Transformer inside the tower as a standard
- Enclosed oil and grease collecting trays

**The innovative cooling concept assures smooth operation in the temperature range from -20°C to +40°C.**

- Three independent cooling circuits: gearbox (oil-cooled), generator (air-cooled), converter (water-cooled)
- Innovative converter cooling method
- Energy efficient temperature controlled cooling systems
- Optional: Hot climate version for unfavorable climate conditions

**By intentionally limiting the turbine dimensions even difficult logistic requirements are met.**

- Standard transport requirements for weight, width, and height are met in many countries, avoiding special and expensive permits
- Reduced crane requirements through its modular design

**The engineering experience of PowerWind GmbH goes from the foundation to the tip of the blade.**

- All design aspects have been reviewed and optimized to increase efficiency
- Foundation designed to simultaneously reduce construction costs and increase stability

**The PowerWind 100 was designed to facilitate servicing and maintenance.**

- Spacious nacelle with good accessibility to all components
- Easy replacement of components due to ergonomic on-board crane
- Application of high quality and maintenance-free components
- Easy access to the hub from inside the nacelle
- Customized service packages available

**PowerWind provides a wide range of support to its customers from the initial project phase throughout the turbine's lifetime.**

- Project and service management support from the initial wind measurement to the scheduling of maintenance and repair
- Large experience with the special requirements of small and medium-size customers

**Performance**

<b>Rated power output</b>	2,500 kW
<b>Cut-in wind speed</b>	3 m/s
<b>Rated wind speed</b>	13 m/s
<b>Cut-out wind speed</b>	25 m/s
<b>Rotor diameter</b>	100 m
<b>Rotor swept area</b>	7,854 m <sup>2</sup>
<b>Rotor speed</b>	3.5 - 14.0 rpm
<b>Speed control</b>	Individual electrical pitch
<b>Aerodynamic breaking</b>	Individual full span pitch
<b>Operating temperature range</b>	-20°C to +40°C (optional to +45°C)
<b>Power factor</b>	0.9 ind. to 0.9 cap.
<b>Wind class</b>	IEC 61400 IIIA and DIBt WZ II
<b>Gearbox</b>	Two planetary and one spur gear
<b>Gear ratio</b>	1:114
<b>Mechanical brake</b>	Disc brake on high speed shaft (hydraulic)
<b>Yaw drive</b>	4 AC motor drives with planetary gear
<b>Yaw brake</b>	Disc brake (hydraulic)

<b>Generator</b>	Synchronous permanent magnet (air-cooled)
<b>Nominal rotation</b>	1,600 rpm
<b>Enclosure class</b>	IP 54
<b>Converter</b>	Full scale converter (water-cooled)
<b>Tower</b>	Steel tower
<b>Hub height</b>	80 m or 100 m
<b>Nacelle</b>	Glass fibre reinforced plastic
<b>Blades</b>	Glass fibre reinforced plastic
<b>Control system</b>	PowerWind
<b>SCADA</b>	PowerWind SCADA System
<b>Grid connection</b>	50 Hz or 60 Hz/690 V

Available from:  
 PowerWind Limited  
 Plot no.352-353  
 HSIIDC Industrial Area Bawal  
 Rewari, Haryana-123501  
 info@powerwind.co.in